

TOP DECK

NATURAL BEAUTY



THE WATERBASED TOPCOAT
FOR A PROTECTED BUT NATURAL-LOOKING WOOD,
RESISTANT TO HIGH FOOT TRAFFIC.



Love wood? Go green!

DISTRIBUTED BY



TOP DECK

WATERBASED TOPCOAT FOR WOOD

NATURAL EFFECT

ADVANTAGES

Top Deck is a clear **waterbased topcoat for wood** containing high resistance UV filters capable of enhancing the natural look of wood while ensuring high protection from any damaging agents, high foot traffic included. Its wax content provides excellent waterproofing to the coated items. Thanks to its acrylic resins based formulation it can be applied also on wooden substrates treated with preservative wood stains or with alkyd coatings.

CHARACTERISTICS

- SUITABLE FOR GARDEN FLOORING AND FURNITURE
- RESISTANT TO HIGH FOOT TRAFFIC AND WEAR AND TEAR
- PREVENTS GRAYING CAUSED BY UV RADIATION
- NATURAL TRANSPARENCY
- KEEPS WOOD NATURAL LOOK UNCHANGED
- HIGH PROTECTION FROM WEATHERING AGENTS
- CONTAINS UV ABSORBERS
- PROTECTS AND MAKES ALL TIMBERS WATERPROOF, INCLUDING EXOTIC WOOD
- SUITABLE ALSO FOR TIMBERS AUTOCLAVE-TREATED WITH SALTS

AREAS OF USE

Exterior woodworks (flooring, decking, garden furniture, balconies, cottages, terraces, verandas, swimming pool edges, gazebos).

ON NEW WOOD

HD2000 can be applied in 1 or 2 coats on bare wood previously sanded with 180 grit sandpaper, or on substrates previously coated with HI20** waterbased wood stains. If necessary, thin from 5 to 10% with water.

ON ALREADY COATED WOOD

If the substrate has already been treated with a wood stain, the surface has to be cleaned and sanded with 180 grit sandpaper. Remove the dust then apply 1 or 2 coats of HD2000 topcoat. If the interval between coats is less than 8 hours, intermediate sanding is not required. In case of extraordinary maintenance, i.e. in case of damaged coating, the old film must be removed completely. Then the surface shall be sanded with 150 grit sandpaper and one shall proceed as specified for application on new wood.



FOR
EXTERNAL
USE



READY TO USE



DRYING:
touch dry: 60 minutes
interval between
coats: 4 hours
through dry: 6 hours



SPREADING RATE:
750 ml = 9 m²



TOOLS:
synthetic
hair brush/spray gun



**TOOLS
CLEANING:**
with water



TOP DECK - WATERBORNE TOPCOAT FOR WOOD NATURAL EFFECT

| CODE | COLOR | PACK SIZE |
|---------|-------|-----------|
| HD 2000 | CLEAR | 0,75 l |
| HD 2000 | CLEAR | 2,5 l |

